



FLOOR STANDING STORAGE TANKS WITH TWO HEAT EXCHANGERS

EV 13/7 S2 1000 101 DN18

Capacity	932 L
Net weight	279 kg
Insulation	100 mm
Heat exchanger surface S1	3.45 m ²
Heat exchanger surface S2	1.31
Heat exchanger capacity S1	31.3 L
Heat exchanger capacity S2	7.9 L
Heat losses ΔT 45K	142 W
Energy class	C
Maximum operational temperature	95 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar



V40 - hot water delivered with a temperature of at least 40°C (S1)	1403 L
V40 - hot water delivered with a temperature of at least 40°C (S2)	604 L
Diameter	1050 mm
Minimum height of the premise	2100 mm



Information

Floor standing storage tanks with two
heat exchangers

EV 13/7 S2 1000 101
DN18

- High-quality enamel coating ensuring long operating life
- Highly efficient PU insulation
- Efficient anode protection
- Service flange for easy inspection of the appliance
- Option for installation of an electric heating element
- Option for installation of a thermal regulator
- Option for installation of a thermal sensor

Serie information

Floor standing storage tanks with two
heat exchangers

EV 13/7 S2 1000
101 DN18

The range includes models with volumes from 160 up to 2000 liters with two heat exchangers. Suitable to cover the demands of a single and multi-family residential buildings or industrial needs.