



FLOOR STANDING STORAGE TANKS WITH TWO HEAT EXCHANGERS

EV 12/8 S2 1500 120 DN18

Capacity	1414 L
Net weight	408 kg
Insulation	100 mm
Heat exchanger surface S1	3.3 m <sup>2</sup>
Heat exchanger surface S2	2.3
Heat exchanger capacity S1	30.4 L
Heat exchanger capacity S2	20.5 L
Heat losses $\Delta T$ 45K	151 W
Energy class	C
Maximum operational temperature	95 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar



V40 - hot water delivered with a temperature of at least 40°C (S1)	1933.8 L
V40 - hot water delivered with a temperature of at least 40°C (S2)	714.1 L
Diameter	1200 mm
Minimum height of the premise	2361 mm



## Information

Floor standing storage tanks with two  
heat exchangers

EV 12/8 S2 1500 120  
DN18

- High-quality enamel coating ensuring long operating life
- Highly efficient PU insulation
- Efficient anode protection
- Service flange for easy inspection of the appliance
- Option for installation of an electric heating element
- Option for installation of a thermal regulator
- Option for installation of a thermal sensor

## Serie information

Floor standing storage tanks with two  
heat exchangers

EV 12/8 S2 1500  
120 DN18

The range includes models with volumes from 160 up to 2000 liters with two heat exchangers. Suitable to cover the demands of a single and multi-family residential buildings or industrial needs.