



			GLSC09EL 9000 Btu/h	GLSC12EL 12000 Btu/h	GLSC18EL 18000 Btu/h	GLSC24EL 24000 Btu/h
Tip			Pompa de caldura aer-aer	Pompa de caldura aer-aer	Pompa de caldura aer-aer	Pompa de caldura aer-aer
Telecomanda			Wireless	Wireless	Wireless	remote controller
Capacitate racire	W		2600(940~3300)	3400(1000~3770)	5100(1250~5910)	6810(1830~7800)
Capacitate incalzire	W		2610(940~3360)	3420(1000~3810)	5100(1250~6070)	6870(1850~7900)
SEER	W/W		6.1	6.1	6.1	6.1
Clasa de energie racire			A++	A++	A++	A++
SCOP	W/W		4	4	4	4
Clasa de energie incalzire			A+	A+	A+	A+
Dezumidificare	Litri/h		1	1.2	1.5	1.8
Putere sonora ui	dB(A)		50/47/43/35/32	50/47/43/35/32	53/50/47/43/36	54/51/48/44/40
Putere sonora ue	dB(A)		60	60	65	67
Presiune sonora ui (S/H/M/L/Mut)	dB(A)		40/37/33/25/22	40/37/33/25/22	43/41/38//35/27	44/41/38/34/30
Putere sonora ue	dB(A)		50	50	55	57
Specificatii electrice						
Alimentare			220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P
Sursa alimentare			Exterior	Exterior	Exterior	Exterior
Curent absorbit	Racire	A	4.0(1.2~8.0)	5.8(1.5~9.0)	8.1(1.7~12.0)	10.7(2.3~12.3)
	Incalzire	A	3.8(1.2~9.0)	5.1(1.5~10.0)	7.0(1.7~13.0)	9.9(2.3~13.5)
Consum	Racire	W	825(240~1380)	1130(290~1500)	1580(330~2340)	2257(410~2824)
	Incalzire	W	767(240~1552)	1005(290~1720)	1374(340~2520)	2063(420~3005)
Tip Refrigerant/Incarcare			R32/0.46kg	R32/0.46kg	R32/1kg	R32/1.14k
Debit	m ³ /h		420	550	800	980
Outdoor fan type			Propeller fan	Propeller fan	Propeller fan	Propeller fan
Connections						
Conexiuni	Gas	Inches	3/8"	3/8"	3/8"	1/2"
	Liquid	Inches	1/4"	1/4"	1/4"	1/4"
Others						
Application area	m ²		9~16	14~22	20~35	27~45
Lungime maxima traseu	m		25	25	25	25
Diferenta maxima de nivel	m		10	10	10	10
Temperaturi limita	UE	°C	Racire:-15-53/Incalzire:-20-30	Racire:-15-53/Incalzire:-20-30	Racire:-15-53/Incalzire:-20-30	Racire:-15-53/Incalzire:-20-30
Dimensiuni nete (W x H x D)	Indoor	mm	698x255x190	777x250x201	910x294x206	1010x315x220
	Outdoor	mm	712x276x459	712x276x459	853x602x349	920x699x380
Greutate neta	Indoor	kg	6.5	7.5	10	13
	Outdoor	kg	22	22	35	40

Filtru carbon Autocuratare Smart Air Flow I FeelKit 3m de montaj Inclus