

# CIRCULATION UNIT

## MIXING FUNCTION, SERIES GRxX00



### PRODUCT DESCRIPTION

The mixing groups are used for the temperature control, mixing function, in heating systems. This means that the heating water prepared in the heating source is mixed down to the desired set temperature, which is then delivered to the heating receiver, e.g. underfloor heating. The units GRxx00 are equipped with rotating mixing valves and actuators. The temperature control, mixing function, is performed based on a signal from an external controller. The mixed temperature is then a result of the controller parameters setting. For example, if the external controller is a weather compensated controller, the mixed temperature will be calculated based on the controller's heating curve settings. The groups are used in systems with controllers, and it depends on the controller type and functions which level of comfort that will be delivered.

Products are equipped with two shut-off valves with colour coded thermometers, a check valve placed on the return line from the heating circuit and an insulation shell. All circulation units are equipped with 3-way rotary mixing valves with progressive characteristic for smooth and precise temperature control, and actuators series ARA600.

When designing the circulation unit product line ESBE focused on performance, design, user friendly usage and environment. This applies to everything from manufacturing, materials to packaging.

### VERSIONS

ESBE mixing function circulation units are available in three different version; standard design with and without pump, and a compact design for areas with limited space .

### SERIES GRA200

The ESBE series GRA200 is a circulation unit equipped with a pump and a 3-way rotary mixing valve with progressive characteristic. The series comes in two sizes, DN25 and DN32 with the possibility of pump choice, Wilo or Grundfos. The pumps can be set to constant speed, variable pressure or constant pressure. The Grundfos pumps come with AutoADAPT feature which adjust the available pump pressure and the flow to the current system requirements.

The circulation units comes with two different versions of actuator; GRA210 with assembled 3-point 230V AC actuator series ARA661, and GRA230 with assembled proportional 24V AC/DC actuator series ARA639. The Series GRA200 has an ESBE QuickFIT interface between actuator and valve that allows for assembly or disassembly of the actuator from the valve without any tools.

The compact design of the unit has been thought through and focus put on components such as pump resulted in high performance of the circulation unit.

### SERIES GRA300

The ESBE series GRA300 is a compact but powerful circulation unit design for applications where space matters, however there is no room for compromises. The GRA300 is a DN20 circulation unit with performance equals the corresponding DN25 groups. This could be possible by adjusting the pump curves and consider the pressure losses in the group. By putting focus on performance, we achieved the smallest circulation unit with unique pump curves which are covering low and high demands.

The GRA300 is equipped with a Wilo pump which can be set to variable or constant pressure, and iPWM1/2. It is also equipped with 3-way rotary mixing valve with progressive characteristic and an assembled 3-point 230V AC actuator series ARA661. Series GRA300 also has an ESBE QuickFIT interface between actuator and valve that allows for assembly or disassembly of the actuator from the valve without any tools.

### SERIES GRF100

The ESBE series GRF100 is a circulation unit with mixing function, available in size DN25, designed to be used with almost any 180mm pump available on the market. The circulation unit is equipped with an insulation shell which can be adjusted according to pump design, even if the pump is delivered with its own insulation.

ESBE have put a lot of effort to make the adjustment process easy and clear, and to make the result of product adjustment like factory assembly.

The series GRF100 are equipped with a 3-way rotary mixing valve with progressive characteristic. It comes in two versions; GRF111 which can be equipped with your preferred actuator or controller, and GRF121 which comes with assembled 3-point 230V AC actuator series ARA661.

### SERVICE AND MAINTENANCE

The circulation unit does not require any specific maintenance under normal conditions.

### KEY BENEFITS

- High class insulation of hydronic parts
- Compact design
- Pre tested and ready to use
- Ready for 180mm pumps - applies to GRF100
- Adjustable insulation shell - applies to GRF100
- Symmetric design for left/right pump placement - applies to GRA200 and GRF100
- Designed to last and perform
- High-end product finish

&gt;&gt;&gt;

# CIRCULATION UNIT

## MIXING FUNCTION, SERIES GRxX00

### RELATED ACCESSORIES

#### ESBE Manifold

Manifolds for Series GRF100 and GRA200. See separate data sheet for further detailed information.

Manifolds for 1, 2, or 3 circulation units with integrated hydraulic separation.

Art. No.

66001100 \_\_\_\_\_ GMA411- for 1 unit

66001600 \_\_\_\_\_ GMA521 - for 2 units

66001700 \_\_\_\_\_ GMA531 - for 3 units

Manifold for 2, 3, 4 or 5 circulation units without integrated hydraulic separation function.

Art. No.

66001200 \_\_\_\_\_ GMA421- for 2 units

66001300 \_\_\_\_\_ GMA431 - for 3 units

66001400 \_\_\_\_\_ GMA441 - for 4 units

66001500 \_\_\_\_\_ GMA451 - for 5 units

Manifold for Series GRA300 without integrated hydraulic separation function. See separate data sheet for further detailed information.

Art. No.


66000500 \_\_\_\_\_ GMA321- for 2 units

66000600 \_\_\_\_\_ GMA331 - for 3 units


# CIRCULATION UNIT

## MIXING FUNCTION, SERIES GRxX00

### PRODUCT ASSORTMENT



GRA211, GRA231



GRA212, GRA232

### SERIES GRA210


Art. No.	Reference	DN	Pump	Connections		Weight [kg]	Note	Replaces
				I	J			
61042100	GRA211	25	Wilco PARA 25/6	G 1"	G 1½"	5,8	230V, 3 point control signal	61040100
61042200		32	Wilco PARA25/8	G 1¼"	G 1½"	6,2		61040400
61042300	GRA212	25	Grundfos UPM3 AUTO 25-50	G 1"	G 1½"	5,9		61040500
61042400		32	Grundfos UPM3 AUTO25-70	G 1¼"	G 1½"	6,1		61040600

### SERIES GRA230

Art. No.	Reference	DN	Pump	Connections		Weight [kg]	Note	Replaces
				I	J			
61042500	GRA231	25	Wilco PARA 25/6	G 1"	G 1½"	5,8	24V, Proportional control signal	61043200
61042600		32	Wilco PARA 25/8	G 1¼"	G 1½"	6,2		61043300
61042700	GRA232	25	Grundfos UPM3 AUTO 25-50	G 1"	G 1½"	5,9		61043400
61042800		32	Grundfos UPM3 AUTO 25-70	G 1¼"	G 1½"	6,1		61043500

# CIRCULATION UNIT


## MIXING FUNCTION, SERIES GRxX00



GRA311

### SERIES GRA300

Art. No.	Reference	DN	Pump	Connections		Weight [kg]	Replaces	Note
				I	J			
61043600	GRA311	20	Wilo PARA STG 15/8	G ¾"	G 1"	4,5	61043100	



GRF111

GRF121

### SERIES GRF100

Art. No.	Reference	DN	Connections		Weight [kg]	Note
			I	J		
61240100	GRF111	25	G 1"	G 1½"	3,4	
61241100	GRF121	25	G 1"	G 1½"	3,8	230V, 3 point control signal

# CIRCULATION UNIT


## MIXING FUNCTION, SERIES GRxX00

**TECHNICAL DATA**

 Visit [esbe.eu](http://esbe.eu) for further detailed information.

**The Circulation unit, in general**

Pressure class: \_\_\_\_\_ PN 10  
 Working pressure: \_\_\_\_\_ 1,0 MPa (10 bar)  
 Connections, \_\_\_\_\_ Internal thread (G), ISO 228/1  
 \_\_\_\_\_ External thread (G), ISO 228/1  
 Insulation: \_\_\_\_\_ EPP λ 0,036 W/mK



Media: \_\_\_\_\_ Heating water (in accordance with VDI2035)  
 \_\_\_\_\_ Water / Glycol mixtures, max. 50%.  
 Water / glycol mixtures are affecting the pump performance. In case of Applications where water / glycol mixtures are used, pump performance should be considered.

**Series GRA211**

Media temperature: \_\_\_\_\_ max. +100°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +55°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN25: \_\_\_\_\_ Wilo PARA 25-130/6-43/SC  
 DN32: \_\_\_\_\_ Wilo PARA 25-130/8-75/SC  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption - Wilo PARA 25/6: \_\_\_\_\_ 3-43 W  
 - Wilo PARA 25/8 \_\_\_\_\_ 10-75 W  
 Enclosure rating: \_\_\_\_\_ IP X4D  
 Insulation class: \_\_\_\_\_ F  
 EEI (Energy Efficiency Index) - Wilo PARA 25/6: \_\_\_\_\_ <0,20  
 - Wilo PARA 25/8: \_\_\_\_\_ <0,21

Valve type: \_\_\_\_\_ Mixing valve VRG432  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

Actuator type: \_\_\_\_\_ ARA661  
 Control signal: \_\_\_\_\_ 3-point  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50 Hz  
 Power consumption: \_\_\_\_\_ 5 VA  
 Running time 90°: \_\_\_\_\_ 120s  
 Enclosure rating: \_\_\_\_\_ IP41  
 Protection class: \_\_\_\_\_ II

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

 LVD 2014/35/EU  
 EMC 2014/30/EU  
 RoHS3 2015/863/EU  
 ErP 2009/125/EU

 SI 2016 No. 1101  
 SI 2016 No. 1091  
 SI 2012 No. 3032  
 SI 2010 No. 2617

PED 2014/68/EU, article 4.3 / SI 2016 No. 1105 (UK)

**Series GRA212**

Media temperature: \_\_\_\_\_ max. +110°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +55°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN25: \_\_\_\_\_ Grundfos UPM3 AUTO 25-50 130  
 DN32: \_\_\_\_\_ Grundfos UPM3 AUTO 25-70 130  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption - Grundfos UPM3 AUTO 25-50: \_\_\_\_\_ 4-33 W  
 - Grundfos UPM3 AUTO 25-70 \_\_\_\_\_ 2-52 W  
 Enclosure rating: \_\_\_\_\_ IP 44  
 Insulation class: \_\_\_\_\_ N/A  
 EEI (Energy Efficiency Index): \_\_\_\_\_ <0,20

Valve type: \_\_\_\_\_ Mixing valve VRG432  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

Actuator type: \_\_\_\_\_ ARA661  
 Control signal: \_\_\_\_\_ 3-point  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50 Hz  
 Power consumption: \_\_\_\_\_ 5 VA  
 Running time 90°: \_\_\_\_\_ 120s  
 Enclosure rating: \_\_\_\_\_ IP41  
 Protection class: \_\_\_\_\_ II

**Material, in contact with water**

Components of: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material of: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

 LVD 2014/35/EU  
 EMC 2014/30/EU  
 RoHS3 2015/863/EU  
 ErP 2009/125/EU

 SI 2016 No. 1101  
 SI 2016 No. 1091  
 SI 2012 No. 3032  
 SI 2010 No. 2617

PED 2014/68/EU, article 4.3 / SI 2016 No. 1105 (UK)

# CIRCULATION UNIT

## MIXING FUNCTION,

### SERIES GRxX00

**TECHNICAL DATA**

 Visit [esbe.eu](http://esbe.eu) for further detailed information.

**Series GRA231**

Media temperature: \_\_\_\_\_ max. +100°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +55°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN25: \_\_\_\_\_ Wilo PARA 25-130/6-43/SC  
 DN32: \_\_\_\_\_ Wilo PARA 25-130/8-75/SC  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption - Wilo PARA 25/6: \_\_\_\_\_ 3-43 W  
 - Wilo PARA 25/8 \_\_\_\_\_ 10-75 W  
 Enclosure rating: \_\_\_\_\_ IP X4D  
 Insulation class: \_\_\_\_\_ F  
 EEI (Energy Efficiency Index) - Wilo PARA 25/6: \_\_\_\_\_ <0,20  
 - Wilo PARA 25/8: \_\_\_\_\_ <0,21  
 Valve type: \_\_\_\_\_ Mixing valve VRG432  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

Actuator type: \_\_\_\_\_ ARA639  
 Control signal: \_\_\_\_\_ proportional  
 Feedback signal: \_\_\_\_\_ 2-10 V  
 Power supply: \_\_\_\_\_ 24 ± 10% V AC/DC, 50/60 Hz  
 Power consumption - Operation, AC: \_\_\_\_\_ 5 W  
 DC: \_\_\_\_\_ 2,5 W  
 Power consumption - Dimensioning, AC: \_\_\_\_\_ 11 VA  
 DC: \_\_\_\_\_ 6 VA  
 Running time 90°: \_\_\_\_\_ 15/30/60/120s  
 Enclosure rating: \_\_\_\_\_ IP41  
 Protection class: \_\_\_\_\_ II

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

 LVD 2014/35/EU SI 2016 Nr. 1101  
 EMC 2014/30/EU SI 2016 Nr. 1091  
 RoHS3 2015/863/EU SI 2012 Nr. 3032  
 ErP 2009/125/EU SI 2010 Nr. 2617

PED 2014/68/EU, artikel 4.3 / SI 2016 Nr. 1105 (UK)

**Series GRA232**

Media temperature: \_\_\_\_\_ max. +110°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +55°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN25: \_\_\_\_\_ Grundfos UPM3 AUTO 25-50 130  
 DN32: \_\_\_\_\_ Grundfos UPM3 AUTO 25-70 130  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption - Grundfos UPM3 AUTO 25-50: \_\_\_\_\_ 4-33 W  
 - Grundfos UPM3 AUTO 25-70 \_\_\_\_\_ 2-52 W  
 Enclosure rating: \_\_\_\_\_ IP 44  
 Insulation class: \_\_\_\_\_ N/A  
 EEI (Energy Efficiency Index): \_\_\_\_\_ <0,20  
 Valve type: \_\_\_\_\_ Mixing valve VRG432  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

Actuator type: \_\_\_\_\_ ARA639  
 Control signal: \_\_\_\_\_ proportional  
 Feedback signal: \_\_\_\_\_ 2-10 V  
 Power supply: \_\_\_\_\_ 24 ± 10% V AC/DC, 50/60 Hz  
 Power consumption - Operation, AC: \_\_\_\_\_ 5 W  
 DC: \_\_\_\_\_ 2,5 W  
 Power consumption - Dimensioning, AC: \_\_\_\_\_ 11 VA  
 DC: \_\_\_\_\_ 6 VA  
 Running time 90°: \_\_\_\_\_ 15/30/60/120s  
 Enclosure rating: \_\_\_\_\_ IP41  
 Protection class: \_\_\_\_\_ II

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

 LVD 2014/35/EU SI 2016 Nr. 1101  
 EMC 2014/30/EU SI 2016 Nr. 1091  
 RoHS3 2015/863/EU SI 2012 Nr. 3032  
 ErP 2009/125/EU SI 2010 Nr. 2617

PED 2014/68/EU, artikel 4.3 / SI 2016 Nr. 1105 (UK)

**Series GRA300**


Media temperature: \_\_\_\_\_ max. +100°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +55°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN20: \_\_\_\_\_ Wilo PARA STG 15-130/8-60/O  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption: \_\_\_\_\_ 2-60 W  
 Enclosure rating: \_\_\_\_\_ IP X4D  
 Insulation class: \_\_\_\_\_ F  
 EEI (Energy Efficiency Index): \_\_\_\_\_ <0,20  
 Valve type: \_\_\_\_\_ Mixing valve VRG438  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

Actuator type: \_\_\_\_\_ ARA661  
 Control signal: \_\_\_\_\_ 3-point  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50 Hz  
 Power consumption: \_\_\_\_\_ 5 VA  
 Running time 90°: \_\_\_\_\_ 120s  
 Enclosure rating: \_\_\_\_\_ IP41  
 Protection class: \_\_\_\_\_ II

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

 LVD 2014/35/EU SI 2016 Nr. 1101  
 EMC 2014/30/EU SI 2016 Nr. 1091  
 RoHS3 2015/863/EU SI 2012 Nr. 3032  
 ErP 2009/125/EU SI 2010 Nr. 2617

PED 2014/68/EU, artikel 4.3 / SI 2016 Nr. 1105 (UK)

# CIRCULATION UNIT

## MIXING FUNCTION, SERIES GRxX00

**TECHNICAL DATA**

 Visit [esbe.eu](http://esbe.eu) for further detailed information.

**Series GRF111**

Media temperature: \_\_\_\_\_ max. +100°C\*  
 \_\_\_\_\_ min. +5°C\*  
 Ambient temperature: \_\_\_\_\_ max. +60°C\*  
 \_\_\_\_\_ min. 0°C\*

\* consider data for choosen pump

Pump type: \_\_\_\_\_ N/A  
 Valve type: \_\_\_\_\_ Mixing valve VRG432  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

PED 2014/68/EU, article 4.3 / SI 2016 No. 1105 (UK)

**Series GRF121**

Media temperature: \_\_\_\_\_ max. +100°C\*  
 \_\_\_\_\_ min. +5°C\*  
 Ambient temperature: \_\_\_\_\_ max. +55°C\*  
 \_\_\_\_\_ min. 0°C\*

\* consider data for choosen pump

Pump type: \_\_\_\_\_ N/A  
 Valve type: \_\_\_\_\_ Mixing valve VRG432  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Close off pressure: \_\_\_\_\_ 200 kPa (2 bar)  
 Leakrate in % of flow\*: \_\_\_\_\_ < 0,05%  
 \* Differential pressure 100kPa (1 bar)

Actuator type: \_\_\_\_\_ ARA661  
 Control signal: \_\_\_\_\_ 3-point  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50 Hz  
 Power consumption: \_\_\_\_\_ 5 VA  
 Running time 90°: \_\_\_\_\_ 120s  
 Enclosure rating: \_\_\_\_\_ IP41  
 Protection class: \_\_\_\_\_ II

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**


 LVD 2014/35/EU  
 EMC 2014/30/EU  
 RoHS3 2015/863/EU  
 ErP 2009/125/EU

 SI 2016 No. 1101  
 SI 2016 No. 1091  
 SI 2012 No. 3032  
 SI 2010 No. 2617


PED 2014/68/EU, article 4.3 / SI 2016 No. 1105 (UK)

**VALVE CHARACTERISTICS, MIXING VALVE VRG430**

Flow [%]



Opening angle [°]



**WIRING**

Please see the Installation Instruction



# CIRCULATION UNIT


## MIXING FUNCTION, SERIES GRxX00

### DIMENSIONING, PUMP CAPACITY DIAGRAM


**Example:** Start with the heat demand of the heating circuit (e.g. 25 kW) and move horizontally to the right in the diagram to the  $\Delta t = 20^\circ\text{C}$  (temperature difference between flow and return of the heating circuit). Next go up and find the possible duty points.

Setting I gives duty point A with a residual head of 40 kPa for DN32. Setting II and III gives duty point B with a residual head of 59 kPa for DN32.


#### SERIES GRA211 – Constant differential pressure, Wilo pump



#### SERIES GRA211 – Variable differential pressure, Wilo pump



#### SERIES GRA211 – Constant speed, Wilo pump





# CIRCULATION UNIT


## MIXING FUNCTION, SERIES GRxX00

### DIMENSIONING, PUMP CAPACITY DIAGRAM


**Example:** Start with the heat demand of the heating circuit (e.g. 30 kW) and move horizontally to the right in the diagram to the  $\Delta t = 15^\circ\text{C}$  (temperature difference between flow and return of the heating circuit). Next go up and find the possible duty points.

Setting I gives duty point A with a residual head of 15 kPa for DN32. Setting II and III gives duty point B with a residual head of 23 kPa for DN32.


### SERIES GRA212 – Constant differential pressure, Grundfos pump



### SERIES GRA212 – Variable differential pressure, Grundfos pump



### SERIES GRA212 – Constant speed, Grundfos pump



# CIRCULATION UNIT


## MIXING FUNCTION, SERIES GRxX00

### DIMENSIONING, PUMP CAPACITY DIAGRAM


**Example:** Start with the heat demand of the heating circuit (e.g. 20 kW) and move horizontally to the right in the diagram to the chosen  $\Delta t$ , which is the temperature difference between flow and return of the heating circuit (e.g. 15°C). Next go up and find the possible duty points.

Setting I gives duty point A with a residual head of 18 kPa. Setting II gives duty point B with a residual head of 32 kPa and III gives duty point C with a residual head of 43 kPa.


#### SERIES GRA311 – Constant differential pressure, Wilo pump



#### SERIES GRA311 – Variable differential pressure, Wilo pump




#### SERIES GRA311 – Ext iPWM 1/ iPWM 2, Wilo pump



# CIRCULATION UNIT MIXING FUNCTION, SERIES GRxX00

## DIMENSIONING, CIRCULATION UNIT CHARACTERISTICS - PRESSURE LOSSES GRF1X1




# CIRCULATION UNIT

## MIXING FUNCTION, SERIES GRxX00

### INSTALLATION EXAMPLES

①



The primary function of the motorized mixing unit (GRx) is flow temperature control, mixing function. The Series GRx are used in heating systems with controllers. The motorized mixing units need an external controller which will measure the flow temperature and control the actuator according to the system needs. The circulation units series GRx are the perfect choice for applications where mixing function is required, and the temperature comfort is set by an external controller.

*The shown applications are only examples of product use!  
Before using the product in any application, the regional and national regulations need to be checked.*